

#### Industrial converter series





#### PC to TV Converter

#### Model:DT-7001

- Automatically detects and converts the incoming PC images to NTSC, PAL.Support high resolution PC input up to SXGA.(1920x1080@60Hz).
- Support resolution: 640x480 60 fps;800x600 60 fps, 75 fps;1024x768 60 fps,75 fps 1280x720 60 fps;1680x 1050 60 fps;1600x1200 60 fps;1920x1080 60 fps.



#### TV to PC Converter

#### Model:DT-7003

- Supports Composite VIDEO(BNC)), S-VIDEO, RGB.
- External Power from 5V@500mA.
- Pure hardware design, just Plug&Play No software or driverRequirement.
- 3D motion adaptive de-interlacing.
- Motion adaptive noise reduction.



#### **BNC TO PC Converter**

#### Model:DT-7003A

- Support resolution:800x600@60HZ/75HZ,1024x768 @60HZ,1280x1024@60HZ,1440x900@60HZ,1680x 1050@60HZ,1920x1080@60HZ,1920x1200@60HZ.
- Input support PAL,NTSC,SECAM standard.
- Adjustable brightness,contrast,sharpness,chroma,hue, etc.,the PIP function.







#### VGA to HDMI Converter

#### Model:DT-7004

- Up-scales VGA to HDMI 1080P.
- Supports VGA Input: 640x480@60/75Hz,1920x1080@60Hz.(Recommended input resol-ution:1024x768@60Hz)
- Supports HDMI Output: 1080P/60Hz.
- Auto-store setting of output resolution.
- Product Dimension:119x74x23 mm (LxWxH).

#### S - Video to HDMI Converter

#### Model:DT-7005

- Convert analog audio and video signals into a single HDMI output for use with HD displays 2 Up-scales Composite Video or S-Video up to full HD 1080p.
- HDMI output is optional at 720P 50Hz/60Hz(LED: red) or 1080P 50Hz/60Hz;(LED:Green).
- Composite Video and S-Video Share the same audio input.

#### YPBPR to HDMI Converter

- Scales general PC resolutions to HDMI 1080p output.
- Scales general HD (480i to 1080p) resolutions to HDMI 1080p output.
- Original scale button control the output screen to any size.
- Automatic detect the component and PC input resolutions format.
- Scaling technology for progressive input resolutions.



### **HDMI to YPBPR Converter**

#### Model:DT-7015

- Connect HDMI sources to a display with YPbPr interface.
- Support full HDMI audio and video.
- No signal loss.
- Suitable for HDCP compliant equipments.
- Plug and play, no software installation required.



#### HDMI to AV/S-Video

#### Model:DT-7019

- Input HDMI Resolution:480p(60Hz),576p(50Hz).
- 720p(50Hz/60Hz),1080i(50Hz/60Hz),1080p(50Hz/60Hz).
- Output Signal: Composite Video.
- (1.0Vpp),S-Video(Y:1.0Vpp,C:0.3Vpp).
- Output Video Systems: PAL/NTSC.
- Output Vid`eo Impedance: 75Ω.
- Compatible with HDMI 1.3 and HDCP.
- Working Temperature: -25°C 75°C.



#### **HDMI** to VGA Converter

- Scales general PC resolutions to HDMI 1080p output.
- Scales general HD resolutions to HDMI 1080p output.
- Original Scaler button control the output screen to any size.
- Provides advanced signal processing with great precision. Colors, resolutions, and details.
- High quality, state of the art motion adaptive de-interlacing for 480i and 1080i input.
- Need DC5V power supply.






#### VGA to HDMI Converter

#### Model:DT-6527

- Input-signal format: 800x600;1024x768;1280x720; 1280x960;1280x1024;1360x768;1600x900;1920x1080.
- Output-signal format: 480p(60Hz);576P(50Hz);720p (50Hz/60Hz);1080i(50Hz/60Hz);1080p(50Hz/60Hz).
- Output impedance:75 Ohm.

#### **HDMI to VGA Converter**

- Input-signal format: 800x600;1024x768;1280x720; 1280x960;1280x1024;1360x768;1600x900;1920x1080.
- Output-signal format: 480p(60Hz);576P(50Hz);720p (50Hz/60Hz);1080i(50Hz/60Hz);1080p(50Hz/60Hz).
- Output impedance:75 Ohm.



### Display to DVI cable

#### Model:DT-6402

- upport Mini DisplayPort 1.1 input and DVI output.
- Support DVI highest video resolution 1080p.
- Powered from DisplayPort source.
- Support ATI Eyefinity 1/2/3/4/5/6 screen display, achieve multiple screens interactive.
- Use to display devices: Computer, Display, project, HD devices.



### Mini display to DVI cable

### Model:DT-6403

- Plug and play, signal transmission stable.
- Conversion chipset inside, no need extra power supply.
- Support ATI Eyefinity1/2/3/4/5/6 screen display,achieve multiple screens interactive.
- Use to Mini display device: Mac book, computer, display etc.



#### HDMI to VGA+AUDIO cable

- Support up to 1920x1080 resolution.
- Plug and play.
- No driver, no external power supply.
- Support HDCP1.0/1.1/1.2.



#### USB to VGA Converter

#### Model:DT-6510

- Screen resolution up to 1600x1200.
- Compatible with all CRT and LED displays.
- Support Windows 2000, XP, Vista, 7,8 and Mac. OS X.



### USB3. 0 TO HDMI Adapter

#### Model:DT-UB092

- Support WIN7, WIN8, WIN10 system.
- Support resolution up to 1920x1080P when connect with USB3.0 interface.
- Support resolution up to 800x600 when connect with USB2.0 interface.
- Support mode:expand,copy,extension,rotating.



#### HDMI to VGA cable

- Support up to 1920\*1080 resolution.
- Plug and play.
- No driver, no external power supply.
- Support HDCP1.0/1.1/1.2.



#### AV to HDMI

#### Model:DT-6518

- AV to HDMI converter.
- Separation:80db(1KHZ).
- Input interface: AV, left and right channel input.
- HDMI signal format:480,576p,720p,1080i,1080p.



#### HDMI to AV

#### Model:DT-6524

- HDMI to AV converter.
- Separation:80db(1KHZ).
- Input interface: AV, left and right channel input.
- HDMI signal format:480,576p,720p,1080i,1080p.



#### WII to HDMI

- Support all wll display modes.
- HDMI Format: 720P/60Hz, 1080P/60Hz.
- Applications: large-screen display, exhibition.
- Finance, research and other.







### SDI TO HDMI Converter (single SDI)

#### Model:DT-6514A

- Auto detect resolution of HD-SDI, SD-SDI and 3G-SDI.
- Full HDMI supported with embedded audio.
- Synchronized output audio video and audio.
- LED Indicator light.
- DC 5V/1A power adapter.

#### SDI+HDMI to HDMI Converter

#### Model:DT-6533

- 1 SDI +1 HDMI INPUT, 1 HDMI OUTPUT
- SDI FORMAT: 3G-SDI, HD-SDI
- HDMI Format: 480I,576I,720I,720P,1080I;1080P.

#### VGA to DVI Converter

- 1 VGA INPUT,1 DVI OUTPUT
- SUPPORT 1920x1200 HIGH Resolution DISPLAY.
- Built-in chip, transformation is stable and effcient.
- Plug and play, do not need to set.

42

# CONVERTER



#### 4K HDMI to HDMI+AUDIO Converter

#### Model:DT-7048

- One channel HDMI input, convert to one channel of HDMI, coaxial, SPDIF+analog2.1.
- HDMI input/output resolution up to 3840x2160@30HZ, support 3D.
- No signal lossing, optimized the transmission of audio and video signal.



### 4K HDMI TO HDMI+VGA+YPbPr+ AUDIO Converter

- One channel HDMI input, convert to one channel of HDMI, coaxial, SPDIF + analog 2.1, VGA and YPbPr ouput.
- HDMI input/output resolution up to 3840x2160@30HZ, support 3D.
- VGA/YPbPr output resolution up to 1920x1080@60HZ (Support applicable models).
- No signal lossing, optimized the transmission of audio and video signal.