

Liberty Platinum Sound System

Technical Specifications



SIX YEAR WARRANTY



Features

Reach Crowds of 1,500+

AC Mode = 125W / DC Mode = 100W

Optional Single or Dual Built-in UHF Wireless with 16 User Selectable Channels

Optional Built-In CD/MP3 Combo Player

Remote Control for CD/MP3 Combo Player

3.5mm input for iPod®

Comes with Standard Built-in Bluetooth

USB Port for Charging MP3 Player/iPod

Two Universal Microphone Input Jacks

Recessed Back Panel Protects Knobs and Ports

True AC/DC or AC only - 110/220V Power Supply

Ceramic Compression Driver

10" Woofer

Proprietary Class D Amplifier


User Replaceable Battery

Charging LED Bar Indicator

Operates 6-8 hours on a Single Charge

Speaker Out to Power Companion Speaker

AC Only Also Available



(LIB-8000CU2 Back Panel Shown)

LIBERTY MODELS AC/DC

- LIB-8000 Liberty with Bluetooth
- LIB-8000U1 Liberty with Bluetooth & 1 wireless receiver
- LIB-8000U2 Liberty with Bluetooth & 2 wireless receivers
- LIB-8000C Liberty with Bluetooth & CD/MP3 combo player
- LIB-8000CU1 Liberty with Bluetooth, CD/MP3 combo player & 1 wireless receiver
- LIB-8000CU2 Liberty with Bluetooth, CD/MP3 combo player & 2 wireless receivers
- LIB-8001 Unpowered companion speaker

UHF WIRELESS

- WH-8000 Wireless handheld microphone/transmitter (540-570 MHz)
- WB-8000 Wireless body-pack transmitter (540-570 MHz) (requires handsfree microphone) Microphone options include:
Over-the-Ear/EM-TA4F, Lapel/LM-60, Collar/CM-60, Headband/HBM-TA4F

TECHNICAL SPECIFICATIONS

Rated Power Output	125 watts AC / 100 watts DC	Mic Inputs:	Lo-Z (1 K Ω), balanced, XLR 12 VDC condenser mic (phantom) power
Max SPL @ Rated Power	117 dB		Hi-Z (10 K Ω), unbalanced, 1/4" phone
Battery	Two 12 V, lead acid rechargeable, 9.0 AH Full recharge: approx 7 hrs		Hi-Z (10 K Ω), unbalanced, 1/8" stereo unbalanced, stereo RCA
Frequency Response	60 Hz - 15 kHz \pm 3dB	Line In	
Line Output (post fader)	isolated, 600 Ω , 1/4" phone	Sensitivity For Rated Output	
AC Power Reqs.	100 - 240 VAC, 50/60 Hz, 300W max	Lo-Z Microphone	-52 dBV (2.5 mVrms)
USB	5V 500mA	Hi-Z Microphone	-43 dBV (7.5 mVrms)
Dimensions (HWD)	22" x 14" x 11.5" (56 x 35.6 x 29.2 cm)	Auxiliary (line)	-14 dBV (200 mVrms)
Weight (AC/DC)	38 lbs / 17 Kg	Phantom Power	36V
Weight (AC only)	26 lbs / 12 Kg	Speaker Out	4-pole Neutrik Speakon® jack

(Features & Specifications Subject to Change Without Notice)



Anchor Audio, Inc.
Portable Sound Systems • Carlsbad, California

800.262.4671
www.anchoraudio.com