

i-2130 SXGA Document Camera Specifications

Model No.	i-2130
Sensor	1/3" CMOS
Total pixel	1.32 Megapixel
Zoom	9x optical, 12x digital
Frame rate	20
Shooting area	Max: 13.5"x10.6", Min: 0.1"x0.1"
Focus	Auto/manual
Native output signal	SXGA(1280x1024@60Hz)
Converted output signal	XGA
Resolution (Horizontal)	≥ 750 TV lines
White balance	Auto/manual
Color adjustment	Yes
Brightness adjustment	Yes
Image capture	Yes, 12 volatile images
Video recording	Yes
Image mirror	Yes
Image rotation	180
Image split	Yes
Image freeze	Yes
Text mode	Yes
Black and white/color conversion	Yes
Positive/negative conversion	Yes
Built-in video scalar	Yes
OSD	Yes
INPUT TERMINALS	
VGA	x2
VIDEO	x1
S-VIDEO	x1
AUDIO	x4
MICROPHONE	x1
OUTPUT TERMINALS	
VGA	x2
VIDEO	x1
AUDIO	x1
S-VIDEO	x1

OTHER TERMINALS	
USB2.0	x1 (USB camera)
USB driver and software	Windows 2000/XP/Vista, Mac OS10.4 or above. Driver plug and play
RS232 (computer controllable)	x1
Remote control	
	Yes
Light source	Arm light×2(LED) A4 size lightbox(LED)
Operating temperature	32°F to 104°F
Dimensions	Folded: 15.9"x16.7"x6.1" Setup: 18.7"x16.7"x22.3"
Power supply	12V DC power adapter
Weight(net)	5Kg

Design and Specifications are subject to change without notice.